



บริษัท ไทย-เกาหลี คาลิเบรชั่น เซ็นเตอร์ จำกัด
Thai – Korea Calibration Center Co., Ltd.



ฝ่ายปฏิบัติการสอบเทียบนอกสถานที่ของ Lab SICT
Institute of Calibration & Technology Co., Ltd. (SICT.)

86/19 หมู่ 3 ต.บึง อ.ศรีราชา ชลบุรี 20230
86/19 Moo. 3 T. Bung A. Sriracha Chonburi (Thailand) 20230
Tel. +66 (0) 38 - 064 536 Fax: +66 (0) 38 - 196 003



ให้บริการด้านการสอบเทียบและปรับเทียบ เครื่องมือวัดอุตสาหกรรม ทั้งในและนอกสถานที่

ตามมาตรฐาน ISO/IEC 17025 : 2017 ด้วยผลการสอบเทียบที่ถูกต้องแม่นยำ และบริการที่รวดเร็ว

จุดมุ่งหมายในการดำเนินงานด้านคุณภาพและการให้บริการแก่ลูกค้า

1. สอบเทียบภายใต้ขอข่ายการรับรองมาตรฐาน ISO/IEC17025: 2017 และความต้องการของลูกค้าอย่างมืออาชีพ
(Calibration under ISO/IEC17025: 2017 and customers requirement with professional manner)
2. ดำเนินการสอบเทียบและส่งคืนเครื่องมือภายใน 5 วันทำการ
(Completed calibration and return UUC within 5 days)
3. บริการสอบเทียบนอกสถานที่ภายใต้ขอข่ายการรับรอง
(Onsite calibration under accreditation scope)
4. บริการฟรี เก็บรายงานผล และประวัติการสอบเทียบด้วยโปรแกรมควบคุมเครื่องมือ (TIMS) 10 ปี
(Free for keep certificate and history by TIMS program 10 Year)
5. บริการรับ-ส่งเครื่องมือฟรี และสามารถให้บริการสอบเทียบในวันหยุดได้
(Non charging of transportation cost and special service in holiday)
6. มอบข้อเสนอในการให้บริการเป็นกรณีพิเศษสำหรับลูกค้าที่ทำสัญญาสอบเทียบ
(Special offers for all long-term calibration contract)
7. ให้คำปรึกษาด้านการวัดและการควบคุมเครื่องมือวัดตามระบบมาตรฐานคุณภาพทุกระบบ
(Consulting, measurement and control instrumentation systems based on all QMS.)



Line ID: sale.tkcc

ติดต่อขอทราบรายละเอียดเพิ่มเติมหรือขอรับบริการได้ที่ website: www.tkcal.net หรือเจ้าหน้าที่

| | | |
|-------------------------|--|--|
| Sale & Service (office) | นส.ชลชาภา โชติรัตน์ นส.สุภาพร สิงคำคา | Mobile: 086-3760772, e-mail: sale@tkcal.co.th Mobile: 038-064536 , e-mail: sale2@tkcal.co.th |
| Managing director : | Mr. Jong Bok Park | Mobile: 081-8621229 e-mail: jongbok.park@sict.co.kr |
| Laboratory Mgr : | นายเด่น จันทพิทักษ์ | Mobile: 086-3010873, e-mail: den@tkcal.co.th |
| Calibration Mgr : | นายรังษิต ปัตถามัง | Mobile: 084-006 4185, 098-248 2330 email: rungsith@tkcal.co.th , rungsith@sict.co.kr |
| Calibration Mgr : | นายประดิษฐ์ แห่่งสนาม | Mobile : 086-111 2591, 084-350 8080 email: pradit@tkcal.co.th , pradit@sict.co.kr |
| Admin & Accounting : | นางสงกรานต์ ไชยมงคล | Mobile : 086-368 9105 e-mail: admin@tkcal.co.th |

| No | Group | Calibration item | Cal Range / Function | Cal Lab./ Type | |
|---|-------|---------------------------------------|--------------------------------|----------------|------------|
| | | | | TKCC. | SICT. |
| Equipment type (Dimension, Hardness, Form, Geometry, Angle) | | | | | |
| 1 | Dim | Vernier, Depth gauge, Caliper gauge | 0 to 1 000 mm (Up to 2 000 mm) | Lab* | Lab*/Site* |
| 2 | Dim | Micrometer external | 0 to 300 mm (Up to 1 000 mm) | Lab* | Lab*/Site* |
| 3 | Dim | 3-Point micrometer, holetest | 2 to 100 mm (Up to 200 mm) | Lab* | Lab*/Site* |
| 4 | Dim | Inside micrometer | 5 to 300 mm | Lab* | Lab*/Site* |
| 5 | Dim | Depth micrometer | 0 to 300 mm | Lab* | Lab*/Site* |
| 6 | Dim | Tubular inside micrometer | 0 to 600 mm (Up to 1 000 mm) | Lab* | Lab*/Site* |
| 7 | Dim | V-anvil micrometer | 1 to 85 mm | Lab | Lab*/Site* |
| 8 | Dim | Height gauge | 0 to 1 000 mm | Lab* | Lab*/Site* |
| 9 | Dim | Dial gauges | 0 to 25 mm | Lab* | Lab*/Site* |
| 10 | Dim | Dial and Digital thickness gauge | 0 to 100 mm | Lab* | Lab*/Site* |
| 11 | Dim | Dial test indicator | 0 to 5 mm | Lab* | Lab*/Site* |
| 12 | Dim | Pin, plain plug and cylindrical gauge | 0.01 to 125 mm (Up to 200 mm) | Lab* | Lab*/Site* |
| 13 | Dim | Go, No go gauge | 0.01 to 125 mm (Up to 200 mm) | Lab* | Lab*/Site* |
| 14 | Dim | Bore / Cylinder gauge | 0 to 1.4 mm | Lab* | Lab*/Site* |
| 15 | Dim | Feeler gauge, Thickness gauge | 0.01 to 3 mm (Up to 10 mm) | Lab* | Lab*/Site* |
| 16 | Dim | Coating thickness, Specimen | 0.01 to 2 mm | Lab* | Lab*/Site* |
| 17 | Dim | Profile projectors | 0 to 300 mm | Site* | Site* |
| 18 | Dim | Measuring Microscopes | 0 to 300 mm | Site* | Site* |
| 19 | Dim | Precision square | 0 to 600 mm | Lab* | Lab* |
| 20 | Dim | Bevel, Universal bevel protractor | 0 to 90 ° (Left/Right) | Lab* | Lab*/Site* |
| 21 | Dim | Radius gauge | 0 to 100 mm (Up to 500 mm) | Lab* | Lab* |
| 22 | Dim | Steel ruler | 0 to 1 000 mm (Up to 2 000 mm) | Lab* | Lab* |
| 23 | Dim | Taper Gauge (Scale type) | 0 to 100 mm | Lab* | Lab* |
| 24 | Dim | Thread plug gauge (Parallel type) | 1 to 105 mm | Lab | Lab* |
| 25 | Dim | Thread ring gauge (Parallel type) | 5 to 200 mm | Lab | Lab* |
| 26 | Dim | Ultrasonic thickness, Specimen | 0.1 to 500 mm | Lab | Lab* |
| 27 | Dim | Gauge block (Grade. 0,1,2) | 0.5 to 100 mm | Lab | Lab* |
| 28 | Dim | Coordinate Measuring Machine (CMM) | 0 to 1 500 mm | Site | Site* |
| 29 | Dim | Precision surface plate | 0 to 250 000 Cm ² | Site | Site* |
| 30 | Dim | Height master | 0 to 600 mm | Lab | Lab* |
| 31 | Dim | Precision level | Dimension, Angle | Lab | Lab* |
| 32 | Dim | Caliper Checker | 0 to 600 mm | Lab | Lab* |
| 33 | Dim | Dial gauge tester | 0 to 25 mm | Lab | Lab*/Site* |
| 34 | Dim | Roughness tester | Ra, Rz (H) | Site | Lab*/Site* |
| 35 | Dim | Electronic micrometer, Comparator | 0 to 5 mm | Lab | Lab*/Site* |

| No | Group | Calibration item | Cal Range / Function | Cal Lab./ Type | |
|---|----------|---|---------------------------------------|----------------|------------|
| | | | | TKCC. | SICT. |
| Equipment type (Mass, Force, Torque, Hardness) | | | | | |
| 36 | Mass | Electric, Electronic, Spring balance | 0 to 300 kg (Up to 1 000 kg) | Lab*/Site* | Lab*/Site* |
| 37 | Force | Push & Pull gauge, Force gauge | 5 N to 1 000 N | Lab* | Lab* |
| 38 | Force | Torque wrench, Torque driver | 0 to 1 000 N.m | Lab* | Lab*/Site* |
| 39 | Mass | Standard Weight | 1 mg to 20 kg | Lab | Lab*/Site* |
| 40 | Torque | Torque meter / Tester | 0.001 to 50 N.m | Lab | Lab* |
| 41 | Hardness | Hardness tester | Rockwell (20~70)HRC | Site | Site* |
| | | | (20~100)HRB | | |
| | | | Vicker Hardness (200~600)HV | Site | Site* |
| | | | (HV0.2,HV0.3,HV0.5,HV1,HV5,HV10,HV30) | | |
| | | | Shore (25 ~ 100)HS | Lab/Site | Site* |
| | | | Rubber, Plastic (0 ~ 100)H | Lab | Lab |
| 42 | Force | Tension / Compression testing machine | 0.1 N to 50 kN | Site | Site* |
| Equipment type (Pressure) | | | | | |
| 43 | Mec | Pressure measuring Instrument (Hydrolic) | 0 to 70 MPa | Lab*/Site* | Lab*/Site* |
| 44 | Mec | Pressure measuring Instrument (Pneumatic) | 0 to 7 000 kPa | Lab*/Site* | Lab*/Site* |
| 45 | Mec | Pressure vacuum gauge (Pneumatic) | -95 to 0 kPa | Lab*/Site* | Lab*/Site* |
| 46 | Mec | Absolute pressure gauge | (5 ~ 7 000) kPa abs | Lab/Site | Lab*/Site* |
| 47 | Mec | Compound pressure gauge | (-95 ~ 2 000) kPa | Lab/Site | Lab*/Site* |
| 48 | Mec | Differential pressure gauge | (0 ~ 2 000) kPa | Lab/Site | Lab*/Site* |
| 49 | Mec | Pressure transducer/Transmitter | (5 ~ 7 000) kPa abs | Lab/Site | Lab*/Site* |
| | | | (0 ~ 70) MPa | Lab/Site | Lab*/Site* |
| Equipment type (Vibration) | | | | | |
| 50 | Mec | Vibration Measuring Instruments | Acceleration (10 ~ 2 500) Hz | Lab | Lab* |
| | | | Velocity (10 ~ 1 250) Hz | | |
| | | | Displacement (10 ~ 630) Hz | | |
| Equipment type (Chemical) | | | | | |
| 51 | Chemical | PH meter (PH) | 4, 7, 10 PH | Lab/Site | - |
| 52 | Chemical | Conductivity Meter (µS) | 84, 1413, 12880 (special 5,10) | Lab/Site | - |

| No | Group | Calibration item | Cal Range / Function | Cal Lab./ Type | |
|--|--------|--|---------------------------------------|----------------|------------|
| | | | | TKCC. | SICT. |
| Equipment type (Electrical Generating & Measurement) | | | | | |
| 53 | E-Meas | Digital & Analog Multimeter (DMM) (AC/DC Volt, AC/DC Current, Resistance) | Full range/ Full function | Lab*/site* | Site* |
| 54 | E-Meas | Resistance meter | 0 to 110 M Ω | Lab* | Site* |
| 55 | E-Gen | Decade resistance box | up to 100 M Ω | Lab* | Lab*/Site* |
| 56 | E-Meas | DC / AC Clamp Meter | 0 to 1 000 A | Lab* | Site* |
| 57 | E-Meas | AC Watt meter (Power meter)(PF = 1) | 0 to 10 kW | Lab*/site* | Site* |
| 58 | E-Meas | Watt hour meter | 60 min to 1 hr | Lab | Lab* |
| 59 | E-Meas | Digital tachometer (Photo-type) | 30 to 99 999 r/min | Lab*/site | Site* |
| 60 | E-Meas | Stroboscope | 60 to 99 999 r/min | Lab*/site | Site* |
| 61 | E-Meas | Universal Counter | Time base 10 MHz (at 1 s) | Lab*/site | Lab*/Site* |
| 62 | E-Meas | Frequency meter | 20 Hz to 1 MHz | Lab* | Lab*/Site* |
| 63 | Gen | Frequency source | 10 Hz to 225 MHz | Lab* | Lab*/Site* |
| 64 | E-Meas | Timer meter (timer relay) | 0.5 to 1200 s | Lab*/site* | Lab*/Site* |
| 65 | E-Meas | Function generators | Full function Ref. Model | Lab* | Lab*/Site* |
| 66 | E-Meas | LCR Meter | Full function | Lab*/site | Lab*/Site* |
| 67 | E-Meas | Oscilloscope / Wave checker | Full function | Lab*/site | Lab*/Site* |
| 68 | E-Meas | ESD meter , Electrostatic voltmeters | 0.5 to 30 kV | Lab* | Lab* |
| 69 | E-Meas | DC Current Shunt (Resistance) | 1 m Ω to 10 Ω | Lab*/site | Site* |
| 70 | E-Gen | DC Power supply (Voltage, Current) | up to 1 000 V, up to 100 A | Lab*/site* | Site* |
| 71 | E-Gen | DC High voltage source | 1 to 10 kV (Up to 50 kV) | Lab*/site* | Site* |
| 72 | E-Gen | DC Electronics load | Full function | Lab*/site* | Lab*/Site* |
| 73 | E-Gen | DC High voltage | 1 to 10 kV | Lab*/site* | Site* |
| 74 | E-Meas | DC Cut-off current | 0.5 to 10 mA | Lab*/site* | Site* |
| 75 | E-Gen | AC Power supply | up to 700 V, up to 15 A | Lab*/site* | Site* |
| 76 | E-Gen | AC High voltage | 1 to 10 kV | Lab*/site* | Site* |
| 77 | E-Meas | AC Cut-off current | 0.5 to 100 mA | Lab*/site* | Site* |
| 78 | E-Gen | Withstanding voltage tester | up to 10kV (AC & DC) | Lab*/site* | Site* |
| 79 | E-Gen | Auto Electrical Safety Analyzer | up to 10kV (AC & DC) | Lab*/site* | Site* |
| 80 | E-Gen | Surge Generators (AC High Voltage) | 0.5 to 10 kV | Lab/site | Site* |
| 81 | E-Gen | Earth tester (continuity) | 5 to 60 A./ (0.05, 0.1, 0.5) Ω | Lab*/site* | Site* |
| 82 | E-Meas | Insulation tester (at 500 to 1 000 V) | 0.4 M Ω to 11 G Ω | Lab*/site* | Site* |
| 83 | E-Meas | Wrist strap / Footwear checker | Full function (up to 10 M Ω) | Lab*/site* | Site* |
| 84 | E-Meas | Audio analyzer & Generator | Full function | Lab/Site | Lab*/Site* |

| No | Group | Calibration item | Cal Range / Function | Cal Lab./ Type | |
|--|--------|--|-------------------------------|----------------|------------|
| | | | | TKCC. | SICT. |
| Equipment type (Electrical Generating & Measurement)-Cont | | | | | |
| 85 | E-Meas | Color Meter / Chroma meter | D65: XYZ & Lab (7 Color) | Lab/site | Site* |
| 86 | E-Meas | Gloss meter | 20 60 85 degree | Lab/site | Site* |
| 87 | E-Meas | Stop watches | 3600 s, 86 400 S, | Lab | Site* |
| 88 | E-Meas | Telephone testers | -5 to -15 dB & 941 to 1477 Hz | Lab/site | Site* |
| 89 | E-Meas | Sound level meter | 94 , 104 dB at 1 kHz | Lab | Lab*/Site* |
| 90 | E-Meas | Attenuator (Frequency) | 0.0 to 60 dB (100MHz to 1GHz) | Lab | Lab* |
| 91 | E-Meas | AC/DC Probe High Volteg | 0 to 6.5 kV | Lab | Lab* |
| 92 | E-Meas | TV Pattern Generator | Full function Ref. Model | Lab | Lab* |
| Equipment type (Temperature) | | | | | |
| 93 | Temp | Temperature indicator & recorder (J,K,T) | -190 to 1 200°C (Simulate) | Lab* | Site* |
| 94 | Temp | Digital thermometer with sensor | -39 to 650 °C | Lab*/site* | Site* |
| 95 | Temp | Analog thermometer with sensor | -40 to 650 °C | Lab*/site* | Site* |
| 96 | Temp | Temp recorder with sensor | -39 to 650 °C | Lab*/site* | Site* |
| 97 | Temp | Resistance thermometer (RTD) | -38 to 300 °C | Lab* | Site* |
| 98 | Temp | Liquid inglass Thermometer | -38 to 200 °C | Lab* | Site* |
| 99 | Temp | Digital Thermo & Hygro meter | -20 to 80 °C, 20 to 95% RH | Lab* | Lab*/Site* |
| 100 | Temp | Dial Thermo - Hygro temperature | 0 to 50 °C, 20 to 95% rh | Lab* | Lab*/Site* |
| 101 | Temp | Thermo - Hygograph | 0 to 50 °C, 20 to 95% RH | Lab* | Lab*/Site* |
| 102 | Temp | Oven & Chamber (Temp & Humidity) | -40 to 200 °C, 20 to 95% RH | Lab*/site* | Lab*/Site* |
| 103 | Temp | Dry block calibrator | -40 to 650°C | Lab/Site | Lab*/Site* |
| 104 | Temp | Oil bath calibrator | -40 to 150°C | Lab/Site | Lab*/Site* |
| 105 | Temp | Water bath Temperature | 0 to 100°C | Lab/Site | Lab*/Site* |
| 106 | Temp | Blackbody Temperature (IR Calibrator) | 0 to 500°C | Lab | Lab*/Site* |
| 107 | Temp | Autoclave Temperature | 50 to 140°C | Lab/Site | Site* |
| 108 | Temp | Tempperature Sensor (Type J,K,T,N & pt100) | -40 to 650 °C | Lab/Site | Lab*/Site* |
| 109 | Temp | Temperature Tranductucers | -40 to 650 °C | Lab/Site | Site* |
| 110 | Temp | Relative humidity transducers | 0-80 °C, 10-95%rh | Lab | Site* |
| 111 | Temp | Infrared thermometer | 0 to 500 °C | Lab | Site* |